

OOS INTERNATIONAL B.V.

SEMI SUBMERSIBLE CRANE / ACCOMMODATION UNIT



revision 4.5

OOS SEROOSKERKE OOS WALCHEREN



OVERVIEW

Semi-Submersible Crane Vessels OOS Serooskerke and OOS Walcheren are multifunctional assets with the ability to offer various services such as: Accommodation, Heavy Lifting, Installation, Modification, Decommissioning, Renewables and Subsea Installation & Removal.

With first-rate station keeping abilities and large crane capacity of 4.400 t in tandem, heavy modules can be placed on the large open deck. In combination with offering the facilities of the Floatel, OOS can deliver turn-key solutions to meet your business needs.

SSCV HIGHLIGHTS

- Unique braceless design
- Hotel capacity is 750 persons on board
- Construction/crane vessel 2x 2.200 t
- Fast compressed air assisted ballast system for quick compensation during lifting operations
- Subsea construction and subsea support up to 3.000 m with Active Heave Compensation up to 5,0 m stroke
- Platform removal and installation
- High transit speed of 11 kn
- DPS-3 with enhanced EHS-P notation
- Excellent proven motion and stationkeeping characteristics
- Low running costs and fuel consumption in both DP and
 Transit Mode due to close-loop (close bus bar) operation







SSCV SPECIFICATION

00S SEROOSKERKE / 00S WALCHEREN

NAME AND BACKGROUND

Estimated delivery date : 00S Serooskerke

Q3 2019

00S Walcheren

Q2 2020

Builders : China Merchants

Heavy Industry

: Marshall Islands Flag/ Port of reg.

Power Management

GENERAL

Classification : ABS

Notation : ₩A1, Column Stabilized Unit, Crane Service, Construction &

Maintenance Service, Accommodation Service, *****AMS, *****ACCU, *****DPS-3, EHS-P, ENVIRO-OS, UWILD,

IHM, CRC, (HC-SUBSEA-PL,OC), HAB+(MODU), SKP,

PMP+, EGC-SCR, ISQM, BWT+

IMO : 9826512 : 137.75 m Length : 81,0 m Beam Depth molded : 12.0 m

Main deck height : 42.80 m from keel

Deck box height : 12.8 m : 11,3 m (excl. Transit draught thrusters) Operating draught

: 20.0 m (excl. thrusters)

Heavy lift draught : 22-26,4 m (excl.

thrusters

: 37.800 t Lightship weight

CARGO CAPACITIES

Clear deck space : 3800 m² Deck Load : 15 ton/m² Variable Deck Load : 6.037 t Transit Pay load : 3.357 t : 2.828 t Fuel Potable water: : 1.642 t : 77,5 t Lub oil

MACHINERY/PROPULSIO

Main Gensets Engine : 8 x STX 8L32/40 MCR 4.000 kW

Propulsion

: 6 x 3.8 mW Thrustmaster

Fixed Pitch Azimuth Thrusters

Underwater Demountable

: Azimuth Thrusters Steering : 11 kn

Speed

System incl. DPS

: Kongsberg Marine

SAFETY

Life boats : 10 x 150 POB

Life rafts : 30 x 25 POB for total 750 POB

ACCOMMODATION

750 POB : 1-Man cabin: 90

: 2-Men cabin: 318 : 4-Men cabin: 6

101 cabins with day light

DECK MACHINERY

ROV

Heavy lift cranes : 2 x 2.200 t @ 22,1 m,

Huisman Capable of tandem lift 4.400 ton and for Subsea Operations up to 3.000 m with Active Heave Compensation up

to 5.0 m Stroke

: 1 x 36 t @ 23,5 m, Huisman Service Cranes

1 x 60 t @ 38,0 m, Huisman

: Telescopic - Hydraulic Type, Gangway

Huisman Nominal Length 39,0 m,

Stroke +7.5 m / -7.5 m

: 4 x SMIT Tow Brackets Towing : (Optional) 8 point mooring Mooring system 1.500 m 76 mm wire

: (Optional) 2 ROV units

Diving : (Optional) SAT Diving Spread





HOLDING OOS INTERNATIONAL GROUP B.V.

The Netherlands

Head Office The Netherlands

00S International B.V. 0ostkapelseweg 4 4353 EH Serooskerke P.O. Box 40 4353 ZG Serooskerke

E: Sales@oosinternational.com T: +31 (0) 118 726 200

Chamber of Commerce No. 20149791 VAT No. NL8204.64.624.B.01

The Netherlands

00S Asia Pacific Pte. Ltd.

00S Singapore

Office 3791 Jalan Bukit Merah #09-24 (E-Centre @ Redhill) Singapore 159471 T: +65 6732 1983

00S China

T: +86 0513 8128 7430

No.1 Xin An Jiang Road, Bin Jiang Street Haimen, Jiangsu Province P.R. China P.C. 226116

00S International do Brazil Servicos Maritimos Ltda.

Rua Internacional 261 - Vale Encantado Macaé - Rio de Janeiro, Brazil CEP 27.933-377 T: +55 22 2020 0500